

FNC F229B15 Series



Features

- Designed for motor feedback applications
- One period sincos signals (Differential 4 Vpp signals)
- A, B, Z incremental
- U, V, W commutation signals
- Differential RS 422 incremental output signals.
- Non-contact magnetic technology
- 22 mm diameter body

Technical data - electrical ratings for sincos out

Voltage supply	5VDC ± %5
Interface	4 Vpp Sine and cosine
Resolution (steps/turn) :	One per revolution

Technical data - electrical ratings for incremental +UVW

Voltage supply	5VDC ± %5
Interface	ABZ ; Line Driver RS422 UVW ; (±24 mA output drive)
Resolution (steps/turn) :	up to 4096 CPR
Commutatiton Signals :	up to 16 pole

Connection for sincos out

Function	Color
+5V	Red
GND	Black
Sin+	Orange
Sin-	Orange-White
Cos+	Blue
Cos-	Blue-White


Connection for incremental out + UVW

Function	Color
+5V	Brown
GND	White
A+	Green
A-	Red
B+	Yellow
B-	Pink
Z+	Gray
Z-	Blue


Technical data - mechanical design

Dimensions	ø22 mm
Mount Diameter	29 mm
Materials	Housing: Aluminium Cover: Aluminium
Magnet actuator	for integration into 6 mm shaft

Pulse Diagram for sincos out




Pulse Diagram for incremental out + UVW




FNC F229B15 Series

Mechanical Dimensions




Magnetic Part Number


F229 MHB0644



F229 MHB0844




F229 MHB1044



FNC F229B15 Series

Installation Guide


Montage



Zero the UVW signals

First move the motor to the required zero UVW position. Short together the two zeroing pads.

zeroing pads



Encoder Part Number

Commutation Version

F **229** **B15** **A** **7** **C**

Outer Diameter
22: 22 mm

Commutation Signals
A : 2 pole
B : 4 pole
C : 6 pole
D : 8 pole
E : 10 pole
F : 12 pole
G : 14 pole
H : 16 pole

Connection Options
C : Cable
M * : Molex 501568-1107 Connector
* (mating with Molex 501330 -1100)

Resolution
7 : 128 ppr / 512 cpr
8 : 256 ppr / 1024 cpr
9 : 512 ppr / 2048 cpr
10 : 1024 ppr / 4096 cpr

Magnet Holder

F **229** **MHB** **0644**

Magnet holder type
0644 : 6 mm hole
0844 : 8 mm hole
1044 : 10 mm hole

Incremental Version

F **229** **B15** **1024** **C**

Outer Diameter
22: 22 mm

Resolution
up to 4096 ppr

Connection Options
C : Cable
M * : Molex 501568-1107 Connector
* (mating with Molex 501330 -1100)